

Quantum search algorithm by adiabatic evolution under a priori probability

Zhaohui Wei and Mingsheng Ying

*State Key Laboratory of Intelligent Technology and Systems,
Department of Computer Science and Technology, Tsinghua University, Beijing, China, 100084*

Grover's algorithm is one of the most important quantum algorithms, which performs the task of searching an unsorted database without a priori probability. Recently the adiabatic evolution has been used to design and reproduce quantum algorithms, including Grover's algorithm. In this paper, we show that quantum search algorithm by adiabatic evolution has two properties that conventional quantum search algorithm doesn't have. Firstly, we show that in the initial state of the algorithm only the amplitude of the basis state corresponding to the solution affects the running time of the algorithm, while other amplitudes do not. Using this property, if we know a priori probability about the location of the solution before search, we can modify the adiabatic evolution to make the algorithm faster. Secondly, we show that by a factor for the initial and final Hamiltonians we can reduce the running time of the algorithm arbitrarily. Especially, we can reduce the running time of adiabatic search algorithm to a constant time independent of the size of the database. The second property can be extended to other adiabatic algorithms.

PACS numbers: 03.67.Lx, 89.70.1c

Quantum search algorithm developed by Grover [1] is one of the main applications of quantum computation. If there is an unsorted database with N items in which there is only one marked item satisfies a given condition, then using Grover's algorithm we will find the object in $O(\sqrt{N})$ steps instead of $O(N)$ classical steps. When the quantum search algorithm was proposed, it was implemented by a discrete sequence of unitary logic gates, which is regarded as the standard paradigm for quantum computing. Now a new quantum computing paradigm based on quantum adiabatic evolution has been proposed [2]. It has been shown that the quantum search algorithm can be implemented by the adiabatic evolution, which also gives rise to a quadratic speed up as Grover's algorithm [3].

In Grover's algorithm and the local adiabatic search algorithm in [3], before search we just know the number of marked items in the unsorted database, and we don't know any further information about the marked item. However, sometimes maybe we know something about some possible locations of the marked item, then we think that perhaps we can use this information to help search. In this paper, we will show that if we know a priori probability about the marked item, we can modify the quantum adiabatic search algorithm to search faster. Then we will show another property of adiabatic search algorithm that conventional quantum search algorithm doesn't have. We can adjust the running time of the algorithm arbitrarily by a factor for the initial and final Hamiltonians of the adiabatic evolution. Especially, we can reduce the running time to a constant time independent of the size of the database. In Grover's algorithm, we can't do this.

To begin, we briefly depict the quantum adiabatic theorem and quantum search algorithm by local adiabatic evolution for later convenience (see [3] for details). Suppose a quantum system with a time dependent Hamiltonian $H(t)$ is in a state $|\psi(t)\rangle$. The quantum adiabatic

theorem says that if the system is initially in the ground state of $H(0)$ and the Hamiltonian varies slowly enough (Suppose the time of the process is T , then T is not very little), the state of the system will stay close to the instantaneous ground state of the Hamiltonian at each time t .

Concretely, suppose H_0 and H_m are the initial and final Hamiltonians of the system, and suppose the system is evolved by the following time dependent Hamiltonian:

$$H(t) = (1 - s)H_0 + sH_m,$$

where $s = s(t)$ is a monotonic function with $s(0) = 0$ and $s(T) = 1$. Let $|E_0, t\rangle$ and $|E_1, t\rangle$ be the ground state and the first excited state of the Hamiltonian at time t , then let $E_0(t)$ and $E_1(t)$ be the corresponding eigenvalues. By the adiabatic theorem we have

$$|\langle E_0; T | \psi(T) \rangle|^2 \geq 1 - \varepsilon^2$$

provided that

$$\frac{D_{max}}{g_{min}^2} \leq \varepsilon, \quad \varepsilon \ll 1, \quad (1)$$

where g_{min} is the minimum gap between $E_0(t)$ and $E_1(t)$

$$g_{min} = \min_{0 \leq t \leq T} [E_1(t) - E_0(t)],$$

and D_{max} is a measurement of the evolving rate of the Hamiltonian

$$D_{max} = \max_{0 \leq t \leq T} |\langle \frac{dH}{dt} \rangle_{1,0}|.$$

Roland and Cerf in [3] showed how to implement quantum search by local adiabatic evolution. We can do as follows. Let

$$H_0 = I - |\psi_0\rangle\langle\psi_0|,$$

$$H_m = I - |m\rangle\langle m|,$$

where

$$|\psi_0\rangle = \frac{1}{\sqrt{N}} \sum_{x=1}^N |x\rangle.$$

$|\psi_0\rangle$, the ground state of H_0 , is the initial state of the system just as in Grover's algorithm, and $|m\rangle$, the destination state of the evolution, is the ground state of H_m . If we evolve the Hamiltonian carefully, after a proper time T we can get the right solution almost determinately by measurement. It is shown that the lower bound of the running time T is

$$T \simeq \frac{\pi}{2\varepsilon} \sqrt{N},$$

which gives rise to a quadratic speed up in contrast to classical algorithms just as Grover's algorithm.

In the above algorithm we have no priori probability about the solution. Suppose we have a priori probability, we use this information to improve our search algorithm. To state our result the following theorem is useful.

Theorem 1 *Suppose we search a unsorted database with N items for one marked item using the adiabatic evolution. If the initial state of the algorithm is*

$$|\psi_0\rangle = \sum_{x=1}^N a_x |x\rangle, \quad 0 < a_m \ll 1,$$

the running time of the algorithm is

$$T \simeq \frac{1}{a_m} \times \frac{\pi}{2\varepsilon},$$

where m is the only marked item of the database.

Proof. We let

$$H_0 = I - |\psi_0\rangle\langle\psi_0|,$$

$$H_m = I - |m\rangle\langle m|,$$

then

$$H(s) = (1-s)(I - |\psi_0\rangle\langle\psi_0|) + s(I - |m\rangle\langle m|).$$

To estimate the running time of the algorithm, we need to estimate D_{max} and $g(s)$, where $g(s)$ is the gap between $E_1(t)$ and $E_0(t)$

$$g(s) = E_1(t) - E_0(t).$$

It is not easy to calculate the eigenvalues of $H(s)$ in the computational basis, and we use the orthonormal basis $\{|\alpha_i\rangle, 1 \leq i \leq N\}$ to eliminate the difficulty, where

$$|\alpha_1\rangle = |m\rangle,$$

$$|\alpha_2\rangle = \frac{1}{\sqrt{1-a_m^2}}(|\psi_0\rangle - a_m|m\rangle),$$

and we don't need to care $|\alpha_i\rangle$, $3 \leq i \leq N$.

Then we have

$$|\psi_0\rangle = \sqrt{1-a_m^2}|\alpha_2\rangle + a_m|\alpha_1\rangle.$$

Now it is not difficult to check that in the new orthonormal basis $H(s)$ will be

$$H(s) = \begin{pmatrix} a_m^2(s-1) - s + 1 & a_m\sqrt{1-a_m^2}(s-1) \\ a_m\sqrt{1-a_m^2}(s-1) & (1-a_m^2)(s-1) + 1 \end{pmatrix}_I,$$

where the empty spaces of the matrix are all zeroes. It is easy to get the eigenvalues of $H(s)$, we denote them by $\lambda_i, 1 \leq i \leq N$, then

$$\lambda_1 = \frac{1}{2} - \frac{1}{2}\sqrt{1-4(1-a_m^2)s(1-s)},$$

$$\lambda_2 = \frac{1}{2} + \frac{1}{2}\sqrt{1-4(1-a_m^2)s(1-s)},$$

and $\lambda_i = 1$ for $3 \leq i \leq N$.

So, we have

$$g(s) = \sqrt{1-4(1-a_m^2)s(1-s)}.$$

On the other hand, It turns out that for arbitrary state $|\alpha\rangle$ we find

$$\langle E_1, t | \alpha \rangle \langle \alpha | E_0, t \rangle \leq \frac{1}{2},$$

which gives

$$|\langle \frac{dH}{ds} \rangle_{1,0}| = |\langle E_1, t | (|\psi_0\rangle\langle\psi_0| - |m\rangle\langle m|) | E_0, t \rangle| \leq 1.$$

According to the adiabatic theorem, the system must evolve under the following condition:

$$|\frac{ds}{dt}| \leq \varepsilon \frac{g^2(s)}{|\langle \frac{dH}{ds} \rangle_{1,0}|}.$$

To make the evolution as fast as possible, we can let $s(t)$ satisfies the equation

$$\frac{ds}{dt} = \varepsilon g^2(s) = \varepsilon [1 - 4(1-a_m^2)s(1-s)].$$

By integral, we can get the lower bound of the running time of the whole evolution

$$T = \frac{1}{\varepsilon} \times \frac{1}{a_m\sqrt{1-a_m^2}} \arctan \frac{\sqrt{1-a_m^2}}{a_m}.$$

Because $a_m \ll 1$, then we have

$$T \simeq \frac{1}{a_m} \times \frac{\pi}{2\varepsilon}.$$

That completes the proof of this theorem. $\square$

We can see that the running time is affected only by a_m , and is independent of $a_x, x = 1, \dots, N, x \neq m$. We can try to think about this property in the standard quantum computation paradigm. In Grover's algorithm, it is difficult to calculate the accurate running time if the initial state is very disordered. Furthermore, the running time of Grover's algorithm is affected by all the amplitudes of the initial state.

Now we use the above result to deal with the search problem under a priori probability. About this problem, we have the following theorem.

Theorem 2 *Suppose we search a unsorted database with N items for a solution using the adiabatic evolution. Before search we have gotten a priori probability,*

$$P(m \in A_i) = p_i \neq 0, \quad \sum_{i=1}^k p_i = 1, \quad 1 \leq i \leq k.$$

Where A_i is a partition of the set $\{1, \dots, N\}$,

$$\cup_{i=1}^k A_i = \{1, \dots, N\}, \quad A_a \cap A_b = \emptyset, \quad 1 \leq a < b \leq k.$$

Then we can improve the performance of search by the priori probability, the new running time is

$$T \simeq \sqrt{\frac{n_M}{p_M}} \times \frac{\pi}{2\varepsilon},$$

where n_i is the number of the items in A_i , and M is the index of the subset that contains the marked item m . The mean running time of the modified algorithm is less than that of original adiabatic search algorithm. For convenience we suppose $p_i/n_i \ll 1$ for $1 \leq i \leq k$.

Proof. The proof is easy if we notice that before search we don't know the location of the marked item and have to set the initial amplitudes averagely in every subset according to the priori probability of the subset. By theorem 1, it can be show that

$$T \simeq \sqrt{\frac{n_M}{p_M}} \times \frac{\pi}{2\varepsilon}.$$

The mean running time of the algorithm is

$$T_{mean} = \sum_{i=1}^k p_i \sqrt{\frac{n_i}{p_i}} \times \frac{\pi}{2\varepsilon}.$$

Using Cauchy-Schwartz Inequality, it is easy to prove

$$T_{mean} \leq \frac{\pi}{2\varepsilon} \sqrt{N},$$

where the quantity appearing on the right hand side of the inequality is the running time of adiabatic search algorithm without priori probability. The equality holds if

and only if every subset has proportional priori probability. $\square$

Now we use some instances to show the effect of Theorem 2. Suppose the partition contains only one subset, the search problem essentially degenerates to the instance without priori probability. It can be shown that the running time is equal to the result in [3]. While If the partition contains two subsets $A_1 = \{1, \dots, N/2 - 1\}$ and $A_2 = \{N/2, \dots, N\}$ with priori probability $p_1 = 0.8$ and $p_2 = 0.2$ respectively, we can find that the running time by Theorem 2 is about 20 percent faster than the result in [3].

By Theorem 2, we have shown that the priori probability about the marked item makes the search performance better. From above we also find that it is convenient to calculate the accurate performance of adiabatic quantum search algorithm with a complicated initial state, while this task is not easy in Grover's algorithm. Besides, adiabatic algorithm has other properties that conventional quantum algorithms don't have. Theorem 3 is one of them.

Theorem 3 *Suppose $H_1(s)$ and $H_2(s)$ are the Hamiltonians of two adiabatic algorithm, and T_1 and T_2 are the running time respectively. If $H_2(s) = cH_1(s)$ for $0 \leq s \leq 1$, then*

$$T_2 = \frac{1}{c} T_1,$$

where $c > 0$.

Proof. We notice that if the Hamiltonian is multiplied by a factor, the eigenvectors don't change and every eigenvalue changes by the same factor. Thus the proof is not difficult. $\square$

In Grover's algorithm, we can't adjust the running time of the algorithm arbitrarily, but in the adiabatic search algorithm we can do this by a factor for the Hamiltonian. Furthermore, this property can be extended to other adiabatic quantum algorithms. So this property can give convenience to us if in the future we use adiabatic evolution to perform some tasks.

To our surprise, we can reduce the running time of adiabatic search algorithm to a constant time independent of the size of the database if we use a proper factor. For example, in [3] if we set the initial and final Hamiltonians as follows,

$$H_0 = \sqrt{N}I - \sqrt{N}|\psi_0\rangle\langle\psi_0|,$$

$$H_m = \sqrt{N}I - \sqrt{N}|m\rangle\langle m|,$$

the running time will change to

$$T \simeq \frac{\pi}{2\varepsilon}.$$

It is a constant time.

In conclusion, we have shown two properties of the adiabatic search algorithm that don't exhibit in the corresponding algorithm of the standard paradigm. By the first one, we have shown that if we search a database under a priori probability, we can use the a priori probability to improve the performance. Moreover, the running time

of adiabatic evolution can be changed arbitrarily by a factor for the Hamiltonians. It seems that sometimes it is more convenient to deal with quantum algorithms by adiabatic evolution than by quantum circuit. In fact, by adiabatic evolution several novel quantum algorithms have been proposed [4][5].

-
- [1] L. K. Grover, Phys. Rev. Lett 79, 325(1997).
 - [2] E. Farhi, J. Goldstone, S. Gutmann, and M. Sipser, e-print quant-ph/0001106.
 - [3] J. Roland and N. J. Cerf, Phys. Rev. A 65, 042308(2002).

- [4] E. Farhi et al. e-print quant-ph/0104129.
- [5] T. D. Kieu, e-print quant-ph/0110136.